

BURAQ**SAE 5W-30****API SP / FULLY SYNTHETIC**

FUEL ECONOMY | FOR GASOLINE ENGINE

Offered In : 1L / 4L / 5L / 20L / 25L / 208L / IBC

DESCRIPTION

MINOC BURAQ SAE 5W-30 API SP is a synthetic engine oil for modern petrol vehicles, including turbocharged and DPF-equipped engines. Keeps engines clean, reduces wear, improves fuel efficiency, and protects emission systems under all driving conditions.

GENERAL CHARACTERISTICS

- Reliable cold-start performance and smooth oil circulation
- Enhanced protection against engine wear and LSPI
- Excellent thermal and oxidation stability at high temperatures
- Maintains engine cleanliness and supports long-term durability

SUITABLE FOR USE IN

- Mercedes
- Land Rover
- Chevrolet
- Mitsubishi
- Volkswagen
- Volvo
- Toyota
- Nissan
- Hyundai
- Renault
- Subaru
- KIA
- BMW
- Mazda
- Daihatsu
- Audi
- Suzuki
- Ford

Disclaimer : Vehicle manufacturer names are used for application reference only and do not imply endorsement, approval or affiliation. Always use the lubricant grade and performance level specified by the vehicle manufacturer.

MEETS & EXCEEDS

API SP, ACEA C3, DEXOS 2 GEN 3,
MB 229.31, 229.51, BMW LL-04,
VW 507.00, RN 0720

TYPICAL PROPERTIES

Test	Unit	Test method	Result
Grade	—	—	5w-30
Density at 15°C	kg/l	ASTM D1298	0.854
Viscosity at 40°C	cSt	ASTM D445	60
Viscosity at 100°C	cSt	ASTM D445	10.5
Viscosity Index (min)		ASTM D2270	≥150
Cold Crank Simulator	cP	ASTM D5293	≤ 6600(-30°C)
Pour Point	°C	ASTM D97	-36
Flash Point	°C	ASTM D92	230
Total Base Number (TBN)	mg KOH/g	ASTM D2896	9

