

POWER DRIVE

SAE 10W-40

API CI-4/SL - FULLY SYNTHETIC

FOR DIESEL ENGINE

Offered In : 1L / 4L / 5L / 20L / 25L / 208L / IBC

DESCRIPTION

MINOC POWER DRIVE SAE 10W-40 API CI-4/SL is a high-performance engine oil formulated for diesel engines. Its advanced viscosity ensures strong lubrication under high temperatures, providing excellent wear protection, oxidation resistance, and engine cleanliness. Suitable for heavy-duty trucks, light commercial vehicles, SUVs. it delivers reliable performance under everyday driving as well as demanding operating conditions.

GENERAL CHARACTERISTICS

- Reliable performance under high-temperature and heavy-load conditions
- Strong protection against engine wear and deposits
- Good thermal and oxidation stability at elevated temperatures
- Maintains engine cleanliness and supports long-term engine durability

SUITABLE FOR USE IN

- Isuzu
- Hino
- Mitsubishi
- Mercedes
- Volvo
- Mack
- Renault
- MAN
- Scania
- Hyundai
- Toyota
- Land Rover
- GMC
- Ford
- Audi
- Chevrolet
- Nissan
- Jeep
- Kia

Disclaimer : Vehicle manufacturer names are used for application reference only and do not imply endorsement, approval or affiliation. Always use the lubricant grade and performance level specified by the vehicle manufacturer.

MEETS & EXCEEDS

API CI-4/SL

ACEA E4 - E7 - A3/B4

GLOBAL DHD-1 - JASO DH-1, Cummins CES 20071/-72/-75/-76/-77/-78, III-05/III-10 - Renault RXD - Scania LDF-2

Detroit Diesel 93K215 - Mack EO-M PLUS, MAN M 3275-1 - MTU Type 3 - Deutz DQC

TYPICAL PROPERTIES

Test	Unit	Test method	Result
Grade	—	—	10w-40
Density at 15°C	kg/l	ASTM D1298	0.866
Viscosity at 40°C	cSt	ASTM D445	89
Viscosity at 100°C	cSt	ASTM D445	13.5
Viscosity Index (min)		ASTM D2270	150
Cold Crank Simulator	cP	ASTM D5293	≤ 7000(-25°C)
Pour Point	°C	ASTM D97	-36
Flash Point	°C	ASTM D92	225
Total Base Number (TBN)	mg KOH/g	ASTM D2896	Min 12

