

POWER DRIVE

SAE 5W-30

API CK-4/SN - FULLY SYNTHETIC

FOR DIESEL ENGINE

Offered In : 1L / 4L / 5L / 20L / 25L / 208L / IBC

DESCRIPTION

MINOC POWER DRIVE SAE 5W-30 API CK-4/SN is a high-performance engine oil formulated for modern diesel and gasoline engines. Its advanced formulation provides excellent wear protection, oxidation stability, soot control, and engine cleanliness under severe operating conditions. Suitable for heavy-duty trucks, light commercial vehicles, SUVs, and other demanding applications, it delivers reliable performance and extended engine protection.

GENERAL CHARACTERISTICS

- Reliable cold-start performance and stable oil circulation in diesel engines
- Strong protection against wear, soot, and deposit formation
- Excellent thermal and oxidation stability under heavy-duty operation
- Maintains engine cleanliness and supports long engine and aftertreatment life

SUITABLE FOR USE IN

- Isuzu
- Hino
- Mitsubishi
- Mercedes
- Volvo
- Mack
- Renault
- MAN
- Scania
- Hyundai
- Toyota
- Land Rover
- GMC
- Ford
- Audi
- Chevrolet
- Nissan
- Jeep
- Kia

Disclaimer : Vehicle manufacturer names are used for application reference only and do not imply endorsement, approval or affiliation. Always use the lubricant grade and performance level specified by the vehicle manufacturer.

MEETS & EXCEEDS

API CI-4/SL - ACEA E4 - E7

A3/B4 - GLOBAL DHD-1 - JASO DH-1

Cummins CES 20071/-72/-75/-76/-77/-78, III-05/III-10 Renault RXD - Scania LDF-2 - Detroit Diesel 93K215,

Mack EO-M PLUS, - MAN M 3275-1 - MTU Type 3 - Deutz DQC

TYPICAL PROPERTIES

Test	Unit	Test method	Result
Grade	—	—	5w-30
Density at 15°C	kg/l	ASTM D1298	0.855
Viscosity at 40°C	cSt	ASTM D445	60
Viscosity at 100°C	cSt	ASTM D445	10.5
Viscosity Index (min)		ASTM D2270	150
Cold Crank Simulator	cP	ASTM D5293	<6600(-30°C)
Pour Point	°C	ASTM D97	-40
Flash Point	°C	ASTM D92	230
Total Base Number (TBN)	KOH/g	ASTM D2896	10

