PRODUCT DATA SHEET

POWER DRIVE
SAE 40

API CF/SF - MINERAL

FOR DIESEL ENGINE
Offered In : 1L / 4L / 5L / 20L / 25L / 208L / IBC

DESCRIPTION

MINOC POWER DRIVE SAE 40 API CF/SF is a high-viscosity engine oil formulated primarily for older diesel engines while also suitable for gasoline engines. It provides reliable lubrication, wear protection, and oxidation resistance under high temperatures. Recommended for use in trucks, light commercial vehicles, agricultural machinery, and construction equipment requiring a CF/SF grade oil.

GENERAL CHARACTERISTICS

- Reliable performance under high-temperature and heavy-load conditions
- Strong protection against engine wear and deposits
- Good thermal and oxidation stability at elevated temperatures
- Maintains engine cleanliness and supports long-term engine durability

SUITABLE FOR USE IN

- Isuzu
- Hino
- Mitsubishi
- Volvo
- Mack
- MAN,
- Scania
- Hyundai
- Toyota
- Nissan
- Jeep
- Kia
- Renault

Disclaimer : Vehicle manufacturer names are used for application reference only and do not imply endorsement, approval or affiliation. Always use the lubricant grade and performance level specified by the vehicle manufacturer.

MEETS & EXCEEDS

API CF/SF
ACEA E3, A3/B3

TYPICAL PROPERTIES

Test	Unit	Test method	Result
Grade	—	—	SAE 40
Density at 15°C	kg/l	ASTM D1298	0.901
Viscosity at 40°C	cSt	ASTM D445	140
Viscosity at 100°C	cSt	ASTM D445	14.5
Viscosity Index (min)		ASTM D2270	103
Cold Crank Simulator	cP	ASTM D5293	-
Pour Point	°C	ASTM D97	-20
Flash Point	°C	ASTM D92	>220
Total Base Number (TBN)	mg KOH/g	ASTM D2896	12

TRIPLE
PROTECTION